

Catalogue No: **2711P-RDT10C**

PVP/PVP CE 1000 TOUCH DISPLAY MODULE

Automation Systems > Operator Panels and Industrial Computers > Operator Panels > PanelView™ Plus 6 Graphic Terminals > PanelView™ Plus 6 1000 Terminals



Representative Photo Only
(actual product may vary based on configuration selections)

PanelView Plus Display Module, 1000 Model, Touch, 10.4 inch TFT Display, Color, No Options

- Faster processor, 512MB memory, and Windows CE 6.0 operating system provide faster response and better graphics
- Modular design includes logic, display, and communication modules
- Recipe management, machine setup, and data-tracking through .csv files
- Built-in PDF viewer for context-sensitive operator support
- Built-in full Unicode font to support multiple languages with a single run-time application
- Base-configured terminal available with display and logic modules
- Supports real-time monitoring of your terminals through a web browser
- RS-232 and Ethernet networks available through built-in communication ports
- Built-in USB ports and SD card slot

SPECIFICATIONS

Component Type	Operator Panel	Display Module
Operator Input Method(s)		Touch
Display Size		10.4 inches
Display Resolution		640x480 pixels
Display Brightness		300 cd/m2
Display Backlight		CCFL (Cold-cathode Fluorescent Lamps)
Display Backlight Life		50000 hours
Touch Screen Type		Resistive
Height, Cutout		224 mm
Width, Cutout		305 mm
Height		248 mm
Width		329 mm
Depth		55 mm
Weight		2.5 kg
IP Rating, Front		IP65
Marine Certified		No
Operating Temperature, Max		55 °C max
Operating Temperature, Min		0 °C min
Storage Temperature, Max		70 °C max
Storage Temperature, Min		-25 °C min
Relative Humidity, Min		5 %RH
Relative Humidity, Max		95 %RH
Software, Configuration		FactoryTalk View Studio Machine Edition
Shock Acceleration (Max.)		15 g
Shock Duration (Max.)		11 ms
Shock Rating		IEC 60068-2-27
Vibration Acceleration (Max.)		2 m/s²

Catalogue No: **2711P-RDT10C**
PVP/PVP CE 1000 TOUCH DISPLAY MODULE

Automation Systems > Operator Panels and Industrial Computers > Operator Panels > PanelView™ Plus 6 Graphic
Terminals > PanelView™ Plus 6 1000 Terminals



Vibration Displacement (Peak to Peak Max.)	0.012 mm
Vibration Frequency, Operational (Max.)	500 Hz
Vibration Rating	IEC 60068-2-6

REFERENCES	
IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-