



CJ1W-ID261

Digital input unit, 64 x 24 VDC inputs, 2 x FCN40 connectors (not included)

Specifications

I/O system	CJ I/O Bus
Expansion unit type	Basic I/O Unit
Type of module	Digital I/O
Number of digital inputs	64
Digital input type	PNP/NPN
Permitted voltage at input	20.4-26.4 V
OFF/ON delay	0-32 ms
Number of digital outputs	0
Digital output type	None
Output current	0 A
Short-circuit protected outputs	✗
I/O connection type	FCN (plug not included)
Number of I/O connectors	2
Detachable I/O terminal block	✗
Suitable for safety functions	✗
Number of IOV (V+) terminals	0
Number of IOG (V-) terminals	0
Number of COM terminals	8
Product Height (unpacked)	90 mm
Product Width (unpacked)	31 mm
Product Depth (unpacked)	66.5 mm
Product Weight (unpacked)	100 g

	G70V-SID16P	Relay terminal, PLC Input, 16 channels, NPN, Push-in terminals
	G70V-SID16P-1	Relay terminal, PLC Input, 16 channels, PNP, Push-in terminals
	P2RVC-8ST-I-5	Interface unit for G2RV-SR/G3RV-ST Push-in, PLC Input, 8 channels, NPN, 30 VAC/DC, Total 2 A, Push-in
	P2RVC-8ST-I-5-1	Interface unit for G2RV-SR/G3RV-ST Push-in, PLC Input, 8 channels, PNP, 30 VAC/DC, Total 2 A, Push-in
	P2RVC-8ST-I-7-1	Interface unit for G2RV-SR/G3RV-ST Screw, PLC Input, 8 channels, PNP, 30 VAC/DC, Total 2 A, Rising-up screw
	XW2D-40G6	General-purpose I/O terminal block, MIL40 socket, M3 captive screws, 40 points
	XW2K-40G-O32A CHN	PLC interface wiring system with push-in plus technology and power supply terminal, 40 points MIL connector, Input/Output, Signal: 0.5 A, Power: 7 A, NPN/PNP, 30 VDC, DIN rail horizontal and vertical mounting
	XW2Z-0100BF-L	I/O connection cable, unshielded, FCN40 to MIL40, 1 m
	XW2Z-0100BN-L	I/O connection cable, unshielded, FCN40 to open ends, 1 m
	XW2Z-0200BF-L	I/O connection cable, unshielded, FCN40 to MIL40, 2 m
	XW2Z-0200BN-L	I/O connection cable, unshielded, FCN40 to open ends, 2 m
	XW2Z-0300BN-L	I/O connection cable, unshielded, FCN40 to open ends, 3 m

	XW2Z-050B	I/O connection cable, FCN40 to MIL40, 0.5 m
	XW2Z-100B	I/O connection cable, FCN40 to MIL40, 1 m
	XW2Z-150B	I/O connection cable, FCN40 to MIL40, 1.5 m
	XW2Z-200B	I/O connection cable, FCN40 to MIL40, 2 m
	XW2Z-300B	I/O connection cable, FCN40 to MIL40, 3 m
	XW2Z-RI200C-175	I/O connection cable, with shield connection, FCN40 to 2 x MIL20, 2 m / 1.75 m

Downloads

CAD Library



CJ1W-ID/IA
Datasheet

EN PDF 3.36 MB



CJ2 CPU Units Hardware
Users Manual

EN PDF 8.4 MB



CJ2-Series
Programmable
Controller
Datasheet

EN PDF 17.9 MB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 24 August, 2026. Click here for [terms of use](#).

